



Model	50 Hz	Motor		Q - Flow								Afmetingen		
		kW	HP	m³/h	0	9	18	24	30	36	42	45	A	DN
				l/min	0	150	300	400	500	600	700	750		
				H - Druk in meters										
636 03	3~220/230 3~380/415	3	4	46	41	36	32	28	23	16	13	536	3"	
636 04	3~220/230 3~380/415	4	5,5	61	55	48	43	37	30	22	17	608	3"	
636 05	3~220/230 3~380/415	5,5	7,5	76	68	59	54	46	38	27	21	671	3"	
636 06	3~220/230 3~380/415	7,5	10	92	82	71	64	56	45	32	26	734	3"	
636 08	3~220/230 3~380/415	9,3	12,5	122	109	95	86	74	60	43	34	860	3"	
636 09	3~220/230 3~380/415	11	15	138	123	107	97	83	68	49	39	923	3"	
636 10	3~220/230 3~380/415	13	17,5	153	137	119	107	93	75	54	43	986	3"	
636 12	3~220/230 3~380/415	15	20	183	164	143	129	111	90	65	51	1112	3"	
636 15	3~220/230 3~380/415	18,5	25	229	205	178	161	139	113	81	64	1301	3"	
636 18	3~220/230 3~380/415	22	30	275	246	214	193	167	135	97	77	1490	3"	
636 21	3~220/230 3~380/415	26	35	321	287	250	225	195	158	113	90	1679	3"	
636 24	3~220/230 3~380/415	30	40	367	328	285	258	222	180	130	103	1868	3"	
636 30	3~220/230 3~380/415	37	50	458	410	357	322	278	225	162	128	2246	3"	

Pomp karakteristiek bij 2850 rpm - ISO 9906