



Model	Motor		Q - Flow									Afmetingen en gewichten				
	kW	HP	m³/h	0	60	78	90	102	120	138	150	Motor	A	B	DN	kg
			l/min	0	1000	1300	1500	1700	2000	2300	2500					
			H - Druk in meters													
8120 01	7,5	10		28	23	20	19	18	15	12	10	6"	560	200	G 5"	37
8120 02	15	20		57	45	41	38	35	30	24	20	6"	705	200	G 5"	49
8120 03	22	30		85	68	61	57	53	45	36	31	6"	850	200	G 5"	61
8120 04	30	40		113	90	81	75	70	60	48	41	6" / 8"	995	200	G 5"	74
8120 05	37	50		142	113	102	94	88	75	60	51	6" / 8"	1140	200	G 5"	86
8120 06	45	60		170	135	122	113	105	90	72	61	6" / 8"	1285	200	G 5"	98
8120 07	55	75		206	167	149	137	125	108	88	75	8"	1430	200	G 5"	110
8120 08	60	80		235	190	170	157	143	123	100	86	8"	1575	200	G 5"	122
8120 09	66	90		265	214	192	176	161	138	113	96	8"	1720	200	G 5"	135
8120 10	75	100		294	238	213	196	179	154	125	107	8"	1865	200	G 5"	147
8120 11	75	100		324	262	234	215	196	169	138	118	8"	2010	200	G 5"	159
8120 12	93	125		353	285	255	235	214	184	150	129	8"	2155	200	G 5"	171
8120 13	93	125		383	309	277	254	232	200	163	139	8"	2300	200	G 5"	184
8120 14	93	125		412	333	298	274	250	215	175	150	8"	2445	200	G 5"	196

Karakteristiek bij 2850 rpm