



Model	50 Hz	Motor		Condens.		Q - Debiet								Afmetingen													
						m³/h		0		3		6		9		12		13,5		15		18		A	B	C	DN
						l/min		0		50		100		150		200		225		250		300					
						H - Druk in meters																					
BS 12 04	1~220/230	1,1	8,4	40	450	26	25	24	21	17	15	13	8	693	307	387	2"										
	3~220/230		4,9																								
	3~380/415		2,8																								
BS 12 06	1~220/230	1,5	10,7	50	450	39	37	36	31	26	23	19	12	829	339	491	2"										
	3~220/230		6,7																								
	3~380/415		3,9																								
BS 12 09	1~220/230	2,2	14,7	70	450	58	56	53	47	39	34	29	18	1124	437	688	2"										
	3~220/230		9,5																								
	3~380/415		5,5																								
BS 12 12	3~220/230	3	13,0			77	74	71	63	52	46	39	24	1278	394	885	2"										
	3~380/415		7,5																								
BS 12 14	3~220/230	3,7	15,5			90	87	83	73	60	53	45	28	1550	520	1030	2"										
	3~380/415		9,0																								
BS 12 16	3~220/230	4	17,2			103	99	95	84	69	61	52	32	1677	543	1134	2"										
	3~380/415		9,9																								
BS 12 22	3~220/230	5,5	21,8			142	137	130	115	95	83	71	44	2139	653	1487	2"										
	3~380/415		12,6																								
BS 12 29	3~380/415	7,5	17,1			187	180	172	152	125	110	94	58	2622	731	1892	2"										

Pomp karakteristiek bij 2850 rpm - ISO 9906