



Model	50 Hz	Motor		Condens.		Q - Debiet								Afmetingen				
		kW	A	uF	V	m <sup>3</sup> /h	0	2,4	4,8	7,2	8,4	9,6	10,8	12	A	B	C	DN
						l/min	0	40	80	120	140	160	180	200				
						H - Druk in meters												
BS 8 04	1~220/230	0,75	5,7	35	450		27	26	25	22	19	16	13	8	581	283	299	2"
	3~220/230		3,5												547	248		
	3~380/415		2,0												695	307		
BS 8 07	1~220/230	1,1	8,4	40	450		47	46	44	38	33	28	22	15	671	283	389	2"
	3~220/230		4,9												787	339		
	3~380/415		2,8												755	307		
BS 8 09	1~220/230	1,5	10,7	50	450		61	59	56	49	43	36	29	19	1046	437	449	2"
	3~220/230		6,7												948	339		
	3~380/415		3,9												1123	394		
BS 8 13	1~220/230	2,2	14,7	70	450		88	85	81	70	62	53	41	27	1123	394	730	2"
	3~220/230		9,5												1411	520		
	3~380/415		5,5												1494	543		
BS 8 17	3~220/230	3	13,0				115	112	106	92	81	69	54	36	1123	394	730	2"
	3~380/415		7,5												1411	520		
BS 8 21	3~220/230	3,7	15,5				142	138	131	114	100	85	67	44	1411	520	891	2"
	3~380/415		9,0												1494	543		
BS 8 23	3~220/230	4	17,2				156	151	143	124	110	93	73	48	1494	543	951	2"
	3~380/415		9,9												1884	653		
BS 8 31	3~220/230	5,5	21,8				210	204	193	168	148	125	98	65	1884	653	1232	2"
	3~380/415		12,6												2333	731		
BS 8 42	3~380/415	7,5	17,1				284	276	262	227	200	170	133	88	2333	731	1603	2"